



PRINT



EMAIL or FAX



GLOSSARY



View Section:

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **1-Part Epoxy Acrylic Concrete & Garage Floor Paint Silver Gray No. 901**

Product Number: 901

Manufacturer Name: BEHR Process Corporation

Address: 3400 W. Segerstrom Avenue
Santa Ana CA 92704

NFPA

U.S. Contact Info.:

Business Phone: (714) 545-7101

Technical Service Phone: (800) 854-0133 ext. 2

Business Fax: (714) 241-1002

1
1 0

Canadian Contact Info.:

Business Phone: (800) 661-1591

Technical Service Phone: (800) 661-1591

Business Fax: (800) 387-0019

HMIS

HEALTH	1
FIRE	1
REACTIVITY	0
PPE	

For Transportation Emergencies:

In the US, call CHEMTREC: (800) 424-9300

In Canada, call CANUTEC: (613) 996-6666 (call collect)

[To Top of page](#)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Product No. 901

Chemical Name	CAS#	Lower Percent	Upper Percent
Styrene acrylic polymers	No data	15	40
Titanium dioxide	13463-67-7	5	10
Monoethylene Glycol	107-21-1	3	7
Additives, dyes, solvents, pigments, emulsifiers, and others	Mixture	3	7
Dipropylene glycol n-butyl ether	29911-28-2	1	5
Dipropylene glycol methyl ether (DPGME)	34590-94-8	1	5
Sodium Lauryl Sulfate, 30%	151-21-3	1	5
Magnesium Aluminum Silicate	12174-11-7	1	5
Amorphous Silica	112926-00-8	1	5
Pigment Black	1333-86-4	1	5
Non-hazardous ingredients		30	60

[To Top of page](#)

SECTION 3: HAZARDS IDENTIFICATION

Product No. 901

Emergency Overview: Irritant.

Applies to all Ingredients

Potential Health Effects:

Eye Contact:	May cause irritation.
Skin Contact:	May cause irritation.
Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Skin Contact:	Prolonged or repeated contact may cause skin irritation.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Aggravation of Pre-Existing Conditions:	None generally recognized.
Guideline Type:	No Information Provided

[To Top of page](#)

SECTION 4: FIRST AID MEASURES

Product No. 901

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

[To Top of page](#)

SECTION 5: FIRE FIGHTING MEASURES

Product No. 901

Flash Point:	No Data
Upper Flammable or Explosive Limit:	No Data
Lower Flammable or Explosive Limit:	No Data
Extinguishing Media:	Use alcohol foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

[To Top of page](#)

SECTION 6: ACCIDENTAL RELEASE MEASURES

Product No. 901

Personal Precautions:	Use proper personal protective equipment as listed in section 8.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.

[To Top of page](#)

SECTION 7: HANDLING AND STORAGE

Product No. 901

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

[To Top of page](#)

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Product No. 901

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable
-----------------------	---

	personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Hand Protection Description:	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Ingredient Guidelines	Guideline Type	Guideline Information
Amorphous Silica		
	ACGIH TLV-TWA	10 mg/m3
	OSHA PEL-TWA	20 mg/m3
Dipropylene glycol methyl ether (DPGME)		
	OSHA PEL-TWA	100 ppm
	ACGIH TLV-TWA	100 ppm
	ACGIH TLV-STEL	150 ppm
Monoethylene Glycol		
	ACGIH TLV-STEL	C 100 mg/m3 (Aerosol only)
Pigment Black		
	ACGIH TLV-TWA	3.5 mg/m3
	OSHA PEL-TWA	3.5 mg/m3
Titanium dioxide		
	ACGIH TLV-TWA	10 mg/m3
	OSHA PEL-TWA	15 mg/m3

[To Top of page](#)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Product No. 901

Physical State/Appearance:	Liquid
Color:	gray
pH:	8.5 to 9.5
Vapor Density:	Greater than 1 (Air = 1)
Density:	9.4-9.9 Lbs./gal.
Molecular Formula:	Mixture
Molecular Weight:	Mixture

[To Top of page](#)

SECTION 10: STABILITY AND REACTIVITY

Product No. 901

Chemical Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.
Incompatibilities with Other Materials:	Oxidizing agents. Strong acids and alkalis.
Hazardous Polymerization:	Not reported.
Hazardous Decomposition	Incomplete combustion may produce carbon monoxide and other toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATIONProduct No. 901

Dipropylene glycol methyl ether (DPGME)

Eye Effect: Eye's - Rabbit : 500 mg/24H; Mild.
Eye's - Human: 8 mg; Mild. (RTECS)

Skin Effects: Skin - Rabbit : 500 mg; Mild. (RTECS)
Skin - Rabbit LD50: 10 mL/kg; Details of toxic effects not reported other than lethal dose value

Chronic Skin Effects: Skin - Rabbit TDLo: 650 mL/kg/13W-I; Behavioral - general anesthetic
Nutritional and Gross Metabolic - weight loss or decreased weight gain Related to Chronic Data - death (RTECS)

Dipropylene glycol n-butyl ether

Eye Effect: Eye's - Rabbit : 100 mg; No effects reported. (RTECS)

Skin Effects: Skin - Rabbit LD50: 5860 uL/kg; Behavioral - somnolence (general depressed activity) Gastrointestinal - hypermotility, diarrhea Lungs, Thorax, or Respiration - other changes

Monoethylene Glycol

Eye Effect: Eye's - Rabbit : 1440 mg/6H; Moderate.
Eye's - rat: 0.000012%/3D; No effects reported. (RTECS)

Skin Effects: Skin - Rabbit : 555 mg; Mild. (RTECS)
Skin - Rabbit LD50: 9530 uL/kg; Details of toxic effects not reported other than lethal dose value

Pigment Black

Skin Effects: Skin - Rabbit LD50: >3 gm/kg; Details of toxic effects not reported other than lethal dose value

Chronic Skin Effects: Skin - rat TDLo: 11 gm/kg/4W-I; Blood - pigmented or nucleated red blood cells
Liver - changes in liver weight Nutritional and Gross Metabolic - weight loss or decreased weight gain (RTECS)

Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans

Sodium Lauryl Sulfate, 30%

Eye Effect: Eye's - Rabbit : 10 mg; Moderate.
Eye's - Rabbit : 100 mg/24H; Moderate. (RTECS)

Skin Effects: Skin - Human: 3%/48H; Moderate.
Skin - Human: 250 mg/24H; Mild. (RTECS)
Skin - Rabbit LDLo: 10 gm/kg; Behavioral - ataxia Gastrointestinal - changes in structure or function of salivary glands Gastrointestinal - hypermotility, diarrhea

Titanium dioxide

Skin Effects: Skin - Human: 300 ug/3D (Intermittent); Mild. (RTECS)

Carcinogenicity: IARC: Group 3: Unclassifiable as to carcinogenicity to humans

[To Top of page](#)

SECTION 12: ECOLOGICAL INFORMATIONProduct No. 901

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

[To Top of page](#)

SECTION 13: DISPOSAL CONSIDERATIONSProduct No. 901

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

[To Top of page](#)

SECTION 14: TRANSPORT INFORMATIONProduct No. 901

DOT Hazard Class: No Data

DOT Identification Number: No Data

[To Top of page](#)

SECTION 15: REGULATORY INFORMATION

Product No. 901

Dipropylene glycol methyl ether (DPGME)

TSCA 8(b): Inventory Status: Listed

Dipropylene glycol n-butyl ether

TSCA 8(b): Inventory Status: Listed

Magnesium Aluminum Silicate

TSCA 8(b): Inventory Status: Not listed

Monoethylene Glycol

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.

Canada DSL: Listed

Pigment Black

TSCA 8(b): Inventory Status: Not listed

Canada DSL: Listed

Sodium Lauryl Sulfate, 30%

TSCA 8(b): Inventory Status: Listed

Canada DSL: Listed

Titanium dioxide

TSCA 8(b): Inventory Status: Listed

Proposition 65: WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

[To Top of page](#)

SECTION 16: ADDITIONAL INFORMATION

Product No. 901

MSDS Preparation Date: 5/2003

MSDS Revision Date: 4/2004

MSDS Author: Actio Corporation

Disclaimer:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

References:

1. American Chemical Society, STN Easy Online Database
2. Brethericks Reactive Chemical Hazards Database. Version 2.
3. Gassarett and Doulls Toxicology, The Basic Science of Poisons.
4. Hawleys Condensed Chemical Dictionary, Thirteenth Edition
5. IARC monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, WHO International Research on Cancer.
6. Industrial Hygiene and Toxicology, by F.A. Patty.
7. National Library of Medicine, Department of Health and Human Services, Hazardous Substances Data Bank (HSDB).
8. National Toxicology Program (NTP) Eighth Report on Carcinogens, 1997.
9. NIOSH Registry of Toxic Effects of Chemical Substances (RTECS) and Pocket Guide to Chemical Hazards.
10. OSHA Hazard Communication Standard, 1910.1200 and Z Tables.
11. Sax Dangerous Properties of Industrial Materials. Tenth Edition.
12. The Merck Index: An Encyclopedia of Chemicals and Drugs. Merck and Company. Twelfth Edition 1998.
13. Threshold Limit Values for Chemical Substances and Physical Agents in the Work Environment and Biological Exposure Indices. TLV Booklet, 2001.

Copyright© 1996-2003 Actio Software Corporation. All Rights Reserved.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

[To Top of page](#)